AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

Claims 1-9. (Canceled)

10. (Currently amended) In a fluid pump for use in a fuel injection apparatus of an internal

combustion engine and having a housing that contains a pump chamber in which at least one

rotary driven delivery element is contained, which delivery element delivers fluid to a

pressure delivery chamber from an intake chamber connected to a reservoir, and having a

pressure limiting valve for limiting the pressure prevailing in the pressure chamber, which

valve has a valve piston inside the housing, the valve piston being acted on in the closing

direction by a prestressed closing spring and being acted on in the opening direction by the

pressure prevailing in the pressure chamber and, when a predetermined pressure in the

pressure delivery chamber is exceeded, opens a connecting conduit from the pressure

delivery chamber to the intake chamber, and a filter preceding the fluid pump and/or a filter,

following the fuel pump, the improvement wherein the fluid pump comprises a pressure

chamber having a connection to a region downstream of the preceding filter or a connection

to a region downstream of the following filter, and wherein the pressure prevailing in the

pressure chamber influences the force on the valve piston in the closing direction in such a

Page 9 of 18

way that as the pressure in the pressure chamber decreases, the force on the valve piston in the closing direction increases.

- 11. (Previously presented) The fluid pump according to claim 10, wherein the pressure chamber is delimited by a moving wall, one side of which is acted on by the pressure prevailing in the pressure chamber and the other side of which is acted on by a prestressed spring that pushes the wall toward the valve piston in its closing direction.
- 12. (Previously presented) The fluid pump according to claim 11, wherein the moving wall is supported against the valve piston by means of a rod.
- 13. (Previously presented) The fluid pump according to claim 11, wherein the moving wall is embodied in the form of a diaphragm.
- 14. (Previously presented) The fluid pump according to claim 12, wherein the moving wall is embodied in the form of a diaphragm.
- 15. (Previously presented) The fluid pump according to claim 10, wherein the valve piston at least partially delimits the pump chamber in the direction of the rotation axis of the at least one delivery element, wherein the closing spring presses the valve piston against the end surface of the at least one delivery element oriented toward it, which end surface functions as

a valve seat, and wherein the pressure prevailing in the pressure chamber acts on at least part

of the end surface of the valve piston oriented toward the at least one delivery element.

16. (Previously presented) The fluid pump according to claim 11, wherein the valve piston

at least partially delimits the pump chamber in the direction of the rotation axis of the at least

one delivery element, wherein the closing spring presses the valve piston against the end

surface of the at least one delivery element oriented toward it, which end surface functions as

a valve seat, and wherein the pressure prevailing in the pressure chamber acts on at least part

of the end surface of the valve piston oriented toward the at least one delivery element.

17. (Previously presented) The fluid pump according to claim 12, wherein the valve piston

at least partially delimits the pump chamber in the direction of the rotation axis of the at least

one delivery element, wherein the closing spring presses the valve piston against the end

surface of the at least one delivery element oriented toward it, which end surface functions as

a valve seat, and wherein the pressure prevailing in the pressure chamber acts on at least part

of the end surface of the valve piston oriented toward the at least one delivery element.

18. (Previously presented) The fluid pump according to claim 13, wherein the valve piston

at least partially delimits the pump chamber in the direction of the rotation axis of the at least

one delivery element, wherein the closing spring presses the valve piston against the end

surface of the at least one delivery element oriented toward it, which end surface functions as

Page 11 of 18

Appl. No. 10/568,812

Amdt. dated November 20, 2008

Reply to Office action of August 22, 2008

a valve seat, and wherein the pressure prevailing in the pressure chamber acts on at least part

of the end surface of the valve piston oriented toward the at least one delivery element.

19. (Currently amended) The fluid pump according to claim 10, wherein the connecting

conduit between the pressure delivery chamber and the intake chamber is embodied in the

form of a groove let into a housing part facing the end surface of the at least one delivery

element and the valve piston controls the passage through this groove.

20. (Currently amended) The fluid pump according to claim 11, wherein the connecting

conduit between the pressure delivery chamber and the intake chamber is embodied in the

form of a groove let into a housing part facing the end surface of the at least one delivery

element and the valve piston controls the passage through this groove.

21. (Currently amended) The fluid pump according to claim 15, wherein the connecting

conduit between the pressure delivery chamber and the intake chamber is embodied in the

form of a groove let into a housing part facing the end surface of the at least one delivery

element and the valve piston controls the passage through this groove.

22. (Currently amended) The fluid pump according to claim 15, wherein, as the pressure

in the pressure delivery chamber increases, the valve piston opens an ever greater through

flow cross section in the connecting conduit.

Page 12 of 18

Appl. No. 10/568,812

Amdt. dated November 20, 2008

Reply to Office action of August 22, 2008

23. (Previously presented) The fluid pump according to claim 15, wherein the diameter of

the valve piston is greater than the width (b) of the connecting conduit.

24. (Previously presented) The fluid pump according to claim 22, wherein the diameter of

the valve piston is greater than the width (b) of the connecting conduit.

25. (Previously presented) The fluid pump according to claim 10, wherein the valve piston

is guided so that it is able to move in a bore of a housing part, and wherein the intake

chamber is connected to a chamber that is delimited in the bore by the rear surface of the

valve piston oriented away from the end surface of the at least one delivery element.

26. (Previously presented) The fluid pump according to claim 11, wherein the valve piston

is guided so that it is able to move in a bore of a housing part, and wherein the intake

chamber is connected to a chamber that is delimited in the bore by the rear surface of the

valve piston oriented away from the end surface of the at least one delivery element.

27. (Previously presented) The fluid pump according to claim 15, wherein the valve piston

is guided so that it is able to move in a bore of a housing part, and wherein the intake

chamber is connected to a chamber that is delimited in the bore by the rear surface of the

valve piston oriented away from the end surface of the at least one delivery element.

Page 13 of 18

Appl. No. 10/568,812

Amdt. dated November 20, 2008

Reply to Office action of August 22, 2008

28. (Previously presented) The fluid pump according to claim 19, wherein the valve piston is guided so that it is able to move in a bore of a housing part, and wherein the intake chamber is connected to a chamber that is delimited in the bore by the rear surface of the valve piston oriented away from the end surface of the at least one delivery element.

29. (Previously presented) The fluid pump according to claim 22, wherein the valve piston is guided so that it is able to move in a bore of a housing part, and wherein the intake chamber is connected to a chamber that is delimited in the bore by the rear surface of the valve piston oriented away from the end surface of the at least one delivery element.